

Low Profile LED Beacons

Bulletin	UK	Export	Issued
1430	YES	YES	11/3/2021







New Vapormatic Low Profile LED Beacons







Vapormatic is pleased to announce the introduction of a new range of low-profile beacons to our popular range of LED products. Particularly useful for operations requiring extra high visibility, this new range features beacons with easy to mount magnetic bases, ultra-low power consumption and long-life performance. All beacons are EMC, ECE R65 rated.



Vapormatic's portfolio of LED work lamps are suitable for many agricultural, commercial and industrial applications and include; heavy-duty 'premium' work lamps, slimline work lamps, LED lightbars, warning beacons, trailer lights and lighting accessories.

To view the full range of Vapormatic LED lighting products, please visit www.vapormatic.com/accessories

Part Number	Description	Product Image	Line Drawing
VLC6160	<p><u>LED amber warning beacon</u> Strong magnetic base designed for service and recovery vehicles where extra high visibility is essential. Amber lens.</p> <ul style="list-style-type: none"> On/Off and change of pattern switch on plug Features and Specifications: Voltage: DC 12-24V Max current: 1.7A@12V, 0.85A@24V Multiple Flash patterns Temperature: -30°C to +50°C ECE R10, ECE R65, CISPR 25 		
VLC6161	<p><u>LED bolt mounted amber warning beacon</u> Designed for service and recovery vehicles where extra high visibility is essential. Amber lens.</p> <ul style="list-style-type: none"> Voltage: DC 12-24V Max current: 1.7A@12V, 0.85A@24V Multiple Flash patterns Temperature: -30°C to +50°C ECE R10, ECE R65, CISPR 25 		
VLC6162	<p><u>Ultra slim LED warning beacon</u> Hard wearing and robust low-profile LED amber beacon with strong magnetic base designed to maximise effectiveness while minimising size.</p> <ul style="list-style-type: none"> Reverse polarity protection Waterproof and vibration resistant design for external or internal use (IP67) On/Off and change of pattern switch on plug Voltage: DC 12-24V Max current: 1.7A@12V, 0.85A@24V Beacon size: 112mm x 46mm 18 LEDs 7 Flash patterns Temperature: -30°C to +60°C ECE R10, ECE R65, CISPR 25 		

<p>VLC6163</p>	<p><u>Ultra slim LED warning beacon</u> Hard wearing and robust DIN mounted flex mounted low-profile LED amber beacon designed to maximise effectiveness while minimising size.</p> <ul style="list-style-type: none"> • Reverse polarity protection • Waterproof and vibration resistant for external or internal use (IP67) • Voltage: DC 12-24V • Max current: 1.7A@12V, 0.85A@24V • Beacon size: Height, 140mm x Width, 112mm • 18 LEDs • 7 Flash patterns • Temperature: -30°C to +60°C • ECE R10, ECE R65, CISPR 25 		
<p>VLC6164</p>	<p><u>LED 595mm long magnetic mounted low-profile amber warning beacon</u> Designed for service and recovery vehicles where extra high visibility is essential. Clear lens.</p> <ul style="list-style-type: none"> • Voltage: DC 12-24V • Max current: 1.7A@12V, 0.85A@24V • Size: 595 x 305 x 56mm • Multiple Flash patterns • On/Off and change of pattern switch on plug • Temperature: -30°C to +50°C • ECE R10, ECE R65, CISPR 25 		
<p>VLC6167</p>	<p><u>LED 595mm long bolt mounted low profile amber warning beacon</u> Designed for service and recovery vehicles where extra high visibility is essential. Clear lens.</p> <ul style="list-style-type: none"> • Voltage: DC 12-24V • Max current: 1.7A@12V, 0.85A@24V • Size: 595 x 305 x 56mm • Multiple Flash patterns • Temperature: -30°C to +50°C • ECE R10, ECE R65, CISPR 25 		
<p>VLC6165</p>	<p><u>LED 310mm long magnetic mounted low-profile amber warning beacon</u> Designed for service and recovery vehicles where extra high visibility is essential. Clear lens.</p> <ul style="list-style-type: none"> • Voltage: DC 12-24V • Max current: 1.7A@12V, 0.85A@24V • Size: 280 x 165 x 45mm • Multiple Flash patterns • On/Off and change of pattern switch on plug • Temperature: -30°C to +50°C • ECE R10, ECE R65, CISPR 25 		
<p>VLC6166</p>	<p><u>LED 310mm long bolt mounted low profile amber warning beacon</u> Designed for service and recovery vehicles where extra high visibility is essential. Clear lens.</p> <ul style="list-style-type: none"> • Voltage: DC 12-24V • Max current: 1.4A@12V, 1.0A@24V • Size: 310 x 159 x 55 • Multiple Flash patterns • Temperature: -30°C to +50°C • ECE R10, ECE R65, CISPR 25 		



All Vapomatic quality replacement parts carry an industry leading **12-month parts and labour warranty**.
For further information on specific items please visit www.vapomatic.com

Original equipment manufacturers names and part number are quoted for reference purposes only and are not intended to infer that our replacement parts are used as original equipment.